

Safety Data Sheet according to WHS Regulations

Printing date 30.04.2021 Revision: 28.04.2021

1 Identification

Product Name: MASONRY ADHESIVE

Recommended Use of the Chemical and Restriction on Use:

Masonary adhesive, plaster jointing compound

Details of Manufacturer or Importer:

USG Boral Building Products Pty Limited (ACN 004 231 976)

251 Salmon Street Port Melbourne VIC 3207

Phone Number: 03 9214 2138

Emergency telephone number: 03 9214 2138

2 Hazard(s) Identification

Hazardous Nature:

Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

The product is not classified, according to the Globally Harmonised System (GHS).

Signal Word None

Hazard Statements None

Precautionary Statements None

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: No reportable hazardous substances or complex substances.

Hazardous Components:

CAS: 1317-65-3 Limestone 10 - 20%

Additional information:

This product may contain small quantities of respirable quartz present as an impurity in the ingredients. Respirable crystalline silica is a known carcinogen and can cause serious lung damage. Exposure to this product is not likely to cause harm under normal conditions, but it is recommended to determine the actual exposure through workplace testing.

Additional ingredients - CAS number not supplied:

Pigment: <1%

Cellulosic thickeners: <1%

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

(Contd. on page 2)

according to WHS Regulations

Printing date 30.04.2021 Revision: 28.04.2021

Product Name: MASONRY ADHESIVE

(Contd. of page 1)

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Ingestion:

If swallowed, do not induce vomiting. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause irritation of the nose and throat and coughing.

Skin Contact: Irritation, redness, pain and rash.

Eye Contact: Irritation, lacrimation, pain and redness.

Ingestion: Gastrointestinal irritation, nausea, vomiting, headache and diarrhoea.

Medical Attention and Special Treatment:

Drinking glycerin, gelatin solutions, or large volumes of water may delay the hardening of this product in the stomach. Surgical relief of obstruction may be required.

5 Fire Fighting Measures

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

Specific Hazards Arising from the Chemical:

May evolve sulphur oxides when heated to decomposition.

This product is not flammable. No fire or explosion hazard exists.

Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe vapours / dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Clean the area using an industrial vacuum cleaner. Wet mopping and wiping is acceptable if vacuuming is not workable. Reuse where possible. Avoid generating dust.

Remove promptly all visible waste materials to avoid being trampled and spread about, place in plastic bags or other containers which prevent fibre and/or dust emission, and dispose of in accordance with local waste disposal authority requirements.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust.

Care should be taken to minimise dust release when opening boxes or bags. Materials should be used and handled in a wet, rather than dry form where workable. Work areas should be cleaned regularly to remove any build up of fibres and/or dust.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment regularly, separate from other laundry to avoid cross-contamination and subsequent skin irritation of non-workers. Provide eyewash fountains or bottled solution or safety showers in close proximity to points of potential exposure.

(Contd. on page 3)

according to WHS Regulations

Printing date 30.04.2021 Revision: 28.04.2021

Product Name: MASONRY ADHESIVE

(Contd. of page 2)

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep containers tightly closed when not in use and protected from physical damage. Protect from heat, sparks, open flames and other sources of ignition. Keep away from aluminium, diazomethane and phosphorus

8 Exposure Controls and Personal Protection

Exposure Standards:	
CAS	: 1317-65-3 Limestone
NES	TWA: 10 mg/m³
CAS: 14808-60-7 Quartz (SiO2)	
NES	TWA: 0.05 mg/m³ respirable dust

Engineering Controls:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below the limits.

Respiratory Protection:

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. At high dust levels, wear a powered air purifying respirator (PAPR) with Class P3 (Particulate) filter or an air-line respirator or a full-face Class P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information. Class L for protection against mechanically generated particulates (dusts and mists) i.e particles generated from operations such as grinding, blasting, spraying and powder mixing, for example, SMF, asbestos, silica, caustic mist and lead.

Airline respirators and powered air-purifying respirators can offer a very high level of respiratory protection. When operated in the positive pressure demand mode these respirators generally reduce problems of poor facial seal. These respirators are usually only required for the most dusty operations or where there are high concentrations of other toxic materials such as crystalline silica or asbestos.

Skin Protection:

Leather/pigskin, PVC or rubber gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting hand protection, the product should comply with relevant performance criteria. For example, gloves should meet a suitable level of abrasion resistance to provide protection against hazards of a workplace.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form: Powder
Colour: Light yellow
Odour: Low odour

Odour Threshold:

pH-Value:

No information available
No information available
No information available
Initial Boiling Point/Boiling Range:
No information available

Flash Point: Not applicable

Flammability: Product is not flammable

(Contd. on page 4)

according to WHS Regulations

Printing date 30.04.2021 Revision: 28.04.2021

Product Name: MASONRY ADHESIVE

(Contd. of page 3)

Auto-ignition Temperature: No information available Decomposition Temperature: No information available

Explosion Limits:

Lower: Not applicable **Upper:** Not applicable

Vapour Pressure: No information available Density: No 2.74 g/cm³ (bulk)

Relative Density: 2.6 - 2.7

Vapour Density: No information available Evaporation Rate: No information available

Solubility in Water: 0.2 %

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of storage and use.

Conditions to Avoid: Heat, sparks, open flames and other ignition sources.

Incompatible Materials:

Heated aluminium, diazomethane, phosphorus (at high temperatures) and oxidising agents.

Hazardous Decomposition Products: Sulphur oxides.

11 Toxicological Information

Toxicity:

Acute Health Effects

Inhalation: May cause irritation of the nose and throat and coughing.

Skin: May cause skin irritation, redness, pain and rash. **Eye:** May cause eye irritation, lacrimation, pain and redness.

Ingestion: May cause gastrointestinal irritation, nausea, vomiting, headache and diarrhoea.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects: No information available

Existing Conditions Aggravated by Exposure: No information available

Additional toxicological information: No information available

(Contd. on page 5)

according to WHS Regulations

Printing date 30.04.2021 Revision: 28.04.2021

Product Name: MASONRY ADHESIVE

(Contd. of page 4)

12 Ecological Information

Ecotoxicity:

Not anticipated to cause any adverse effects to plants or animals based on the main component(s).

Aquatic toxicity: No information available

Persistence and Degradability: No information available Bioaccumulative Potential: No information available

Mobility in Soil: No information available

Other adverse effects: No information available

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulatedProper Shipping Name Not regulatedDangerous Goods Class Not regulatedPacking Group: Not regulated

15 Regulatory Information

Australian Inventory of Industrial Chemicals:

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Poison Schedule:

Not a scheduled poison.

16 Other Information

Date of Preparation or Last Revision: 28.04.2021

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society)

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Disclaimer

This SDS is prepared in accord with the New Zealand Chemical Industry Council document 'Code of Practice (No. HSNO CoP 8-1 09-06)'.

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. USG Boral Building Products Pty Limited makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet.

MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.